



Client:	
Order #:	
Project:	
Type:	

DESCRIPTION

The VSW LED fixture blends the familiar aesthetic of a traditional wraparound luminaire with advanced LED technology to deliver a durable and highly adaptable lighting solution. Engineered for performance and longevity, its streamlined design makes it well-suited for industrial, commercial, and institutional environments. The VSW provides consistent, energy-efficient illumination, offering dependable operation and enhanced lighting quality across a wide range of applications.

FEATURES

- Up to 150 Lumens per Watt
- Sensor and EM Solution ready
- Mounting: Surface (Standard) or Suspended.
- Features a sleek and modern design that enhances any space
- Available in 2ft and 4ft length

CONSTRUCTION & ELECTRICAL

- Frosted PMMA lens
- Universal 120-277VAC
- 12V Aux Power & 0-10V Dimming
- Suitable for damp locations
- Built to last with a projected lifetime of over 100,000 hours

PERFORMANCE DATA

CRI

80+

CCT

3000K, 4000K, 5000K

Projected Lifetime

>196,000 Hours (L70)
>60,000 Hours (L90)

Dimming

0-10V Dimming Standard,
10% down to 100%

Operating Temperature

-20°C (-4°F) to 50°C (122°F)

Warranty

5 year Standard

ORDERING INFORMATION

VSW / / / / / / / / / /

SERIES SIZE WATTAGE CCT VOLTAGE DRIVER FEATURES FINISH CONTROLS EMERG. BATT. WARRANTY

FIXTURE SERIES	
VSW	Classic Style Wrap
SIZE	
2	2FT Nominal Length
4	4FT Nominal Length
WATTAGE	
25WS	15W, 20W, 25W Select. (2,190lm - 3,750lm) (2FT)
35WS	25W, 30W, 35W Select. (3,650lm - 5,250lm) (4FT)
CCT	
CS	80+ CRI, 30K, 40K, 50K CCT Select.
VOLTAGE	
UNV	Universal 120-277VAC

DRIVER FEATURES	
12A	12V Aux Power & 0-10 V Dimming
FINISH	
WH	White Finish
CONTROLS	
MWI	Motion Sensor, Microwave Occ., Line Voltage, Internal Mount
MDLPEL	Motion Sensor, PIR Occ., Daylight Harvesting, Plug'n'Play, Elbow Mount
EMERGENCY BATT. BACKUP	
EM8	8W Emergency Battery Back Up
WARRANTY	
-	5 Year Warranty (Standard)

PERFORMANCE DATA

VSW 25WS 1 X 2							
SETTING	SYSTEM WATTS	3000K		4000K		5000K	
		LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)
LV1	15 W	2,190 lm	146 lm/W	2,250 lm	150 lm/W	2,220 lm	148 lm/W
LV2	20 W	2,920 lm	146 lm/W	3,000 lm	150 lm/W	2,960 lm	148 lm/W
LV3	25 W	3,650 lm	146 lm/W	3,750 lm	150 lm/W	3,700 lm	148 lm/W

VSW 35WS 1 X 4							
SETTING	SYSTEM WATTS	3000K		4000K		5000K	
		LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)	LUMENS (80CRI)	LPW (80CRI)
LV1	25 W	3,650 lm	146 lm/W	3,750 lm	150 lm/W	3,700 lm	148 lm/W
LV2	30 W	4,380 lm	146 lm/W	4,500 lm	150 lm/W	4,440 lm	148 lm/W
LV3	35 W	5,110 lm	146 lm/W	5,250 lm	150 lm/W	5,180 lm	148 lm/W

DIMENSIONS

unit: mm/inch

